



Power Supply Kits	24VDC External Power Adapter Terminal (24V, 24W, 3-Pin) (1200036)	48VDC External Power Supply Adapter, Bare Wires (48VDC, 120W, 2-Wire) (1200048)	24VDC External Power Adapter Bare Wires (24VDC, 24W, 3-Wire) (1200038)	5VDC External Power Adapter, Barrel Power (5VDC, 15W, 2.1MM Barrel Connector) (1200037)
-------------------	---	---	--	---

FEATURES

Related Products	DeviceMaster RTS/UP	RocketLinX Managed PoE Switch	DeviceMaster RTS, RocketLinX ES8510-XT	DeviceMaster RTS 1-Port DB9
Standards	North American / European	North American / European	North American / European	North American / European
Output	24VDC	48VDC	24VDC	5VDC
Operating Range	90 - 264VDC, 47-63Hz	90 - 264VDC, 47-63Hz	90 - 264VDC, 47-63Hz	90 - 264VDC, 47-63Hz
Output Connector	3-pin Terminal Block	Bare Wires	Bare Wires	2.1MM diameter Barrel
Operating Temperature	-37° to 74° C	0° to 40° C	-37° to 74° C	-37° to 74° C



Power Cords	Australia Power Cord Kit (1200052)	China Power Cord Kit (1200049)	India Power Cord Kit (1200051)	Japan Power Cord Kit (1200050)	UK Power Cord Kit (1200053)
-------------	------------------------------------	--------------------------------	--------------------------------	--------------------------------	-----------------------------

FEATURES

Length	8 feet	8 feet	8 feet	8 feet	8 feet
24VDC External Power Adapter, Terminal (24V, 24W, 3-pin)	Yes	Yes	Yes	Yes	Yes
24VDC External Power Adapter, Bare Wires (24VDC, 24W, 3-Wire)	Yes	Yes	Yes	Yes	Yes
5VDC External Power Adapter, Barrel Power (5VDC, 15W, 2.1MM Barrel Connector)	Yes	Yes	Yes	Yes	Yes
48VDC External Power Adapter, Bare Wires (48VDC, 120W, 2-Wire)	Yes	Yes	Yes	Yes	Yes